



**TECHNICAL SPECIFICATIONS:**

- A** | FRAME SILL WIDTH | 3 1/16"
- B** | FRAME SILL HEIGHT | 3 3/8"

- **Clean Vertical Operation**  
 Features a fixed upper sash and a vertically sliding lower sash for effortless, space-saving use.
- **Secure Locking Mechanism**  
 Integrated safety lock ensures reliable closure and user peace of mind.
- **Thermal Efficiency**  
 Engineered with high-performance insulation to support energy savings and interior comfort.
- **Modern Architectural Fit**  
 Slim, sleek aluminum profile blends seamlessly into contemporary residential or commercial facades.
- **Low Maintenance Durability**  
 Corrosion-resistant aluminum frame offers long-lasting performance with minimal upkeep.

**GLASS TYPE**

PVB	SGP
3/16" + 0.09" (PVB) + 3/16" HEAT STREND' D GLASS LAMINATED GLASS	3/16" + 0.09" (SGP) + 3/16" HEAT STREND' D GLASS LAMINATED GLASS
1/4" + 0.09" (PVB) + 1/4" HEAT STREND' D GLASS LAMINATED GLASS	1/4" + 0.09" (SGP) + 1/4" HEAT STREND' D GLASS LAMINATED GLASS
5/32" + 3/8" AIR SPACE + 5/32" + 0.09" (PVB) + 5/32" HEAT STREND' D GLASS INSULATED LAMINATED GLASS	5/32" + 3/8" AIR SPACE + 5/32" + 0.09" (SGP) + 5/32" HEAT STREND' D GLASS INSULATED LAMINATED GLASS

Glazing Bar Layout