



FL
APPROVAL



SOUND
PERFORMANCE



WATER
ISOLATION

- Durable Stainless Steel Driver ensures long-lasting, smooth operation
- Horizontally sliding sash design for easy and practical use
- Window latch and sash lock for strength and security
- Precision rollers for quiet and effortless gliding
- Clean and modern profile compatible with various architectural styles




TECHNICAL SPECIFICATIONS:

A | FRAME JAMB WIDTH | 3"

B | FRAME JAMB HEIGHT | 4"



GLASS TYPE

	PVB	SGP
	3/16" + 0.09" (PVB) + 3/16" HEAT STREN'D GLASS LAMINATED GLASS	3/16" + 0.09" (SGP) + 3/16" HEAT STREN'D GLASS LAMINATED GLASS
	1/4" + 0.09" (PVB) + 1/4" HEAT STREN'D GLASS LAMINATED GLASS	1/4" + 0.09" (SGP) + 1/4" HEAT STREN'D GLASS LAMINATED GLASS
	5/32" + 3/8" AIR SPACE + 5/32" +0.09" (PVB) + 5/32" HEAT STREN'D GLASS INSULATED LAMINATED GLASS	5/32" + 3/8" AIR SPACE + 5/32" +0.09" (SGP) + 5/32" HEAT STREN'D GLASS INSULATED LAMINATED GLASS