



TECHNICAL SPECIFICATIONS:

- A | FRAME HEAD WIDTH | 3 7/8 "
- B | FRAME HEAD HEIGHT | 2 13/16 "

"Available in bi-fold designs with up to **14 operable panels.**"

GLASS TYPE

PVB	SGP
 3/16" + 0,09" (PVB) + 3/16" HEAT STREN'D GLASS LAMINATED GLASS	 3/16" + 0,09" (SGP) + 3/16" HEAT STREN'D GLASS LAMINATED GLASS
 1/4" + 0,09" (PVB) + 1/4" HEAT STREN'D GLASS LAMINATED GLASS	 1/4" + 0,09" (SGP) + 1/4" HEAT STREN'D GLASS LAMINATED GLASS
 5/32" + 3/8" AIR SPACE + 5/32" +0,09" (PVB) + 5/32" HEAT STREN'D GLASS INSULATED LAMINATED GLASS	 5/32" + 3/8" AIR SPACE + 5/32" +0,09" (SGP) + 5/32" HEAT STREN'D GLASS INSULATED LAMINATED GLASS

- Three Point Lock System**
Integrated three-point locking mechanism enhances security and ensures firm closure across multiple panels.
- Smooth Folding Operation**
Precision-engineered rollers and hinges provide effortless, quiet folding movement for daily comfort.



FL
APPROVAL



SOUND
PERFORMANCE



WATER
ISOLATION



RESIDENTIAL THRESHOLD

