

**TECHNICAL SPECIFICATIONS**

SIDE FRAME PROFILE	3 5/16 " / 5 1/4 "
BOTTOM FRAME PROFILE	1 " / 5 1/4 "
MOTOR BOX PROFILE	5 9/16 " / 5 1/4 "
ADAPTER SASH PROFILE	2 7/16 " / 4 1/16 "
SASH PROFILE	1 3/16 " / 1 3/8 "
INTERLOCK SASH PROFILE	1 11/16 " / 1 3/8 "

**APPLICATION FEATURES**

EASY CLEANING SYSTEM	✓
MAXIMUM INSULATION	✓
HIDDEN DESIGN	✓
EASY SERVICE & INSTALLATION	✓
SAFE USE DETAIL	✓
RICH SYSTEM VARIATIONS	✓

Experience Open-Space Comfort  
All Year Round

- **Motorized Guillotine Technology:**  
Provides remote-controlled vertical movement with a chain-driven silent system.
- **Panoramic Usage Advantage:**  
Offers maximum openness for cafés, restaurants, terraces, and balconies, creating spacious living areas.
- **Fixed Railing Function:**  
Can be safely used as a glass railing system when fully opened.
- **Insulated Compatible Structure:**  
Applicable with 4-16-4 and 6-12-6 tempered insulated glass combinations.
- **Panel Options:**  
Offers 2-panel or 3-panel production alternatives according to the application area.

