


- Sash Carrying Capacity:**
400 lbs standard / 660-880 lbs with HBSB mechanism
- Integrated Fly Screen:**
Fly screen design is seamlessly integrated into the system on all frame types
- Sash Connection Options:**
45° and 90° corner joint alternatives available for sash assembly
- High Durability and Smooth Operation:**
Stainless steel rail system combined with specially designed bearings ensures long-lasting performance and enhanced user comfort

TECHNICAL SPECIFICATIONS	
SASH WIDTH	2 4/16"
SASH LENGTH	3 10/16"
FRAME LENGTH	1 12/16"
GLASS THICKNESS	13/16" - 1 12/16"
MAX. SASH CARRYING CAPACITY	440 lbs / 660-880 lbs
INSULATION BRIDGE	15/16"

APPLICATION FEATURES	
HBSB MECHANISM	✓
FLYSCREEN	✓
45° AND 90° SASH JOINT	✓
40 & 50 MM THICKNESS OPTIONS IN MEDIUM SEAM	✓
INNER AND EXTERIOR FLOORING FACING SAFE	✓
EASE OF USE AND FUNCTIONALITY	✓
MONO RAIL FRAME	✓
3 TRACK FRAME	✓

High thermal performance
with polyamide barrier.

Stainless steel rail



Slim Mullion Detail
With its slim mullion design, the system enhances aesthetics while bringing more natural light and wider views into your living spaces.

