

GLR54 SLIM;
A thermally insulated, **inward-opening aluminium** window system with a **concealed sash**, designed to meet the **aesthetic expectations of modern architecture**.

MINIMAL APPEARANCE
MAXIMUM VIEW

FLYSCREEN
DESIGN

SOUND
PERFORMANCE

WATER
INSULATION

TECHNICAL SPECIFICATIONS

3 3/8"	SASH WIDTH
2 3/16"	FRAME TO SASH HEIGHT
3 3/8"	FRAME WIDTH
1" - 1 1/8"	GLAZING THICKNESS
1 5/16"	THERMAL BARRIER
264 - 441 lbs	MAX. SASH WEIGHT CAPACITY

(UW) 1,10 W/m²K

SYSTEM FEATURES

Concealed Sash Design ✓

Thermal Insulation ✓

Inward-Opening Window System ✓

Reliable Hardware Solutions ✓

Minimal and Seamless Design

The concealed sash and slim profile geometry create a clean, minimalist and seamless façade appearance.

Enhanced Weathertightness

The adjustable locking hardware provides improved resistance to air and water infiltration while enhancing acoustic insulation.

Minimized sash profile visibility creates a clean, uniform and visually seamless façade appearance.

09 www.linearossadesign.com

Aluminum Architectural Systems Product Catalog 10